

## PXY 38

### *compact 2-axes translation stages*

#### **Concept:**

The systems of the series PXY 38 are ideally suited for nm-precise positioning of optic components such as mirrors and laser diodes, adjustment and mounting in semiconductor technologies and electronics, and applications in measurement technologies and quality assurance as well as microbiology.

The series PXY 38 consist of piezo electrical actuator in stage design with a solid top and bottom plate for easily integration in optical setups. The monolithic flexure hinges design offers high precision motion range, high stiffness and in due of this excellent dynamical performance for extremely fast and accurate positioning tasks.

#### **Specials:**

With the use of a control signal, the X and Y-axis can be controlled separately. The axis are located orthogonal to each other and the direction of motion is show by small markings on the stage. As an option they may come equipped with strain gage or capacitive position sensors, depending on the system configuration, to achieve very accurate repeatability in the low nanometer range. The systems of this series are available in vacuum and cryogenic temperature configurations.

#### **Interfaces:**

The elements of the series PX are actuators integrated with an inner lever transmission in housing. Since the lever mechanism works in both directions, pulling forces between bottom and top plate need to be avoided, as they could damage the stage. The stage is fixed to a base plate.

Components can be mounted on the top plate by two threaded diagonal holes and can be accurately affixed using the precise pin holes.



image: PXY 38

#### *Product highlights:*

- accurate parallel motion
- up to 38 $\mu$ m motion range
- without mechanical play
- easily combined with other piezo electrical systems
- precision pin holes for accurate adjustment
- high dynamic range

#### *Applications:*

- fiber positioning
- 2D-scanning systems
- beam alignment
- semiconductor
- micro manipulation

## PXY 38

### Technical data:

linear positioning stage	unit	PXY 38	PXY 38 SG
<b>part no.</b>		T-201-00	T-201-01
<b>axis</b>	-	X,Y	X,Y
<b>motion in open(±10%)/closed loop (±0.2%)*</b>	µm	38/ -	38/32
<b>capacitance (±20%)**</b>	µF	0.7	0.7
<b>resolution (open/closed loop)***</b>	nm	0.07/ -	0.07/0.7
<b>integrated measurement system</b>	-	-	strain gage
<b>typ. repeatability</b>	nm	-	±1.5
<b>typ. non-linearity</b>	%	-	0.03
<b>resonant frequency (unloaded)</b>	Hz	730/1090	730/1090
<b>max. push/pull forces</b>	N in x	59/6	59/6
	N in y	53/5	53/5
<b>stiffness x/y</b>	N/µm	1.55/1.4	1.55/1.4
<b>voltage range</b>	V	-20...130V	-20...130V
<b>connector (additional variation please see table below) ****</b>	-	LEMO 0S.302	LEMO 0S.302/ LEMO 0S.304
<b>cable length</b>	m	1	1.2
<b>temperature range</b>	°C	-20°C ... +80°C	-20°C ... +80°C
<b>material</b>	-	aluminum/stainless steel	
<b>dimensions (LxWxH)</b>	mm	25x25x16	40x40x23
<b>weight</b>	g	45	100

\* typical value measured with NV 40/3 amplifier (closed loop: NV 40/3 CLE amplifier )

\*\* typical value for small electrical field strength

\*\*\* the resolution is only limited by the noise of the power amplifier and metrology

\*\*\*\* additional connectors configuration examples please see table blow

Product name	Description	Specials	Part. No Suffix.
PXY 38 Digital	Version for digital controller series d-Drive and 30DV50 in combination with additional functionalities	Connector Sub-D 15	T-201-00D
PXY 38 SG Extern	Version with sensor pre-amplifier for the use with „CLE“ amplifier units and with the additional functionalities: Interchangeability, ASI	Sensor-Connector ODU 4pin	T-201-01E

Rights reserved to change specifications as progress occurs without notice!